

UPSMODEM



Specifications

MODEL	UPSmodem
TECHNOLOGY	DC Ups
AC INPUT	
Voltage Range	90 VAC ~ 264 VAC
Frequency	50 o 60 Hz
DC OUTPUT	
Voltage	12 Vdc $\pm$ 5%
Max. Power	25W (2.1A)
BATTERY	
Type	Lithium-ion Battery
Nominal Voltage	3.7 Vdc
Capacity	2600 mAh
Typical Charging time	3 hours recover to 90% capacity
PHYSICAL	
Input Plug	Italian type
Output cable	1m Length DC Male Jack
Adapters	5,5 x 2,1 mm (female) – 5,5 x 2,5 mm C (male) 5,5 x 2,1 mm (female) – 4,8 x 1,7 mm F (male) 5,5 x 2,1 mm (female) – 3,5 x 1,35 mm H (male)
Dimension, DxWxH (mm)	68 x 42 x 74
Net Weight	280g

Approximate Back-up Time Table

MODEL	UPSmodem
Backup time	Min 30' - Max 3h (depends on the Modem type)



Naicon

UNIT



Diloc



Elsist



Naicon srl Via il Caravaggio, 25 Trecella I 20060 Pozzuolo Martesana - Milano (Italy)
Tel. +39 02 95.003.1 Fax +39 02 95.003.313 www.naicon.com e-mail: naicon@naicon.com